


*A Division of the Angelus Corporation*Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com
N220 W1051 Springdale Road, Waukesha, WI 53186Approved : *JMG*

Date : 10/21/03

Rev. 2 : (10/17/22)

Distribution : User

Uncontrolled if Printed

RJ45 Ethernet Plug Connector*(Contacts @ Positions 1, 2, 3, and 6 only)***PERFORMANCE**Meets or Exceeds Cat 5E
EIA / TIA 568A for the 2-pair

Current / Voltage: 1.5 Amps @ 30 VAC / 42 VDC

ENVIRONMENTAL

Temperature Rating -40° C to +70° C

Insertion / Extraction 1000 cycles

CONNECTOR WEIGHT

tbd

RoHS COMPLIANT

Complies to RoHS Standards

REQUIRED TOOLINGCrimp Tool P/N 110340
(Alternate) P/N 110274**CONSTRUCTION****Materials:**

Plug Housing	Polycarbonate, 94-V0
Contacts	Phosphor Bronze, .012" thk
Rear Shield	Copper Alloy
Inner Ferrule	Copper Alloy
Strain Relief Sleeve	Thermoplastic Rubber, 94-V0

Finish :

Contacts	Gold
Rear Shield	Nickle
Inner Ferrule	Nickle

APPLICABLE STANDARDS

FCC 68

Notes :

- 1) Please refer to T-190007, or T-190007-SQ1 Termination Instruction sheet for strip dimensions & instructions.