



PIC Wire & Cable	Connector Specification	P/N 190104
A Division of the Angelus Corporation Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com PO Box 330 Sussex, WI 53089	Approved : 	Date 08/05/03 Rev. 3 (06/16/14)
	Distribution : USER	Uncontrolled Document

HN Straight Plug
for S44191, S44193, S46191
or RG400, RG142



Features Not Shown : Safety Wire Holes, Gasket in Front

PERFORMANCE

Nominal Impedance	50 Ohms
Frequency Range	0 - 4 GHz
Voltage Rating	1500 VRMS
Insulation Resistance	5000 Megohms

CONNECTOR WEIGHT (Each)

1.78 ounces (50.46 grams)

RoHS COMPLIANT

Complies to RoHS standards

INSTALLATION

Pic Die Set

Center Contact
M22520 / 5 - 01 Tool,
PIC 190118 Hex Crimp Die
(.098 hex)

Crimp Ferrule
M22520 / 5 - 01 Tool,
PIC 190118 Hex Crimp Die
(.213/.261 hex)

MIL Spec Die Set

Center Contact
M22520 / 5-01 Tool,
MIL Spec *M22520 / 5-57
(.100 B hex)

Crimp Ferrule
M22520 / 5-01 Tool,
MIL Spec *M22520 / 5-57
(.213 A hex)

CONSTRUCTION

Materials:

Body	Brass, ASTM-B16, Alloy UNS 36000, H02
Center Contact	Brass, ASTM-B16, Alloy UNS 36000, H02
Ferrule	Brass, ASTM-B16, Alloy UNS 36000, Dead Soft, Weatherseals included
Dielectric	TFE Fluorocarbon, ASTM-D1710, Type 1, Grade 1

Finish :

Body, Ferrule	Nickel
Center Contact	Gold

Applicable Standards	Mil-Std 348 Mil-C-3643
-----------------------------	---------------------------

Notes :

- 1) A 2.5" piece of Raychem ATUM heat shrink P/N ATUM-16/4-0 provided with connector for purpose of strain relief & moisture protection.
- 2) Please refer to T-190XXX Termination Instruction sheet for strip dimensions & instructions.

* Note - MIL Spec die to be used on the smaller diameter area of ferrule only. Not the larger "Bell" areas on each end.

PIC Wire & Cable Connector User specification sheets are non-controlled documents. Please contact PIC Wire and Cable or visit the PIC website (www.picwire.com) to ensure the latest revision of the drawing is being viewed.