
## 

## RJ45 Plug Connector - Shielded Cat 5e / Cat 6

(For conductors with an OD range of 0.037 to 0.042") (fits Amphenol RJ Type ruggedized housing)



## **PERFORMANCE**

## CONSTRUCTION

Exceeds ANSI/TIA/EIA Cat 5e	Materials:	
Performance Tuned to CAT 6 cables	Plug Housing	Polycarbonate

Current/Voltage 1.5 Amps @ 30 VAC/42 VDC Contacts Phosphor Bronze, 0.012" thick

Contact Resistance 10 milliOhms Max Load Bar Polycarbonate

ENVIRONMENTAL Shielding Brass, Alloy 70/30, 1/4 HD

Temperature Rating - 40° C to + 85° C Strain Relief Thermoplastic Rubber - UL 94-VO

Insertion/Extraction 1000 Cycles *Finish*:

Shield Tin Flame Auto Extinguish UL 94-VO Contacts Gold

**CONNECTOR WEIGHT (Each)** 

0.10 ounces (2.835 grams) Applicable Standards: ANSI/TIA-1096-A ANSI/TIA/EIA 568-C.2

RoHS COMPLIANT

Complies to RoHS Standards (1) Please refer to T-110361 Termination Instruction Sheet for strip dimensions & instructions.

Notes:

REQUIRED TOOLING (1)

Crimp Tool P/N 110288