


RJ45 Plug Connector - Shielded Cat 5e/Cat 6

(For conductors with an OD range of 0.044 to 0.048") (For E10424, E40424, E12424 - must use compression tool*)



PERFORMANCE

CONSTRUCTION

Exceeds ANSI/TIA/EIA Cat 5e	
Performance Tuned to CAT 6 cables	

Current/Voltage 1.5 Amps @ 30 VAC/42 VDC

Contact Resistance 10 milliOhms Max

ENVIRONMENTAL

Temperature Rating -40° C to $+85^{\circ}$ C

Insertion/Extraction 1000 Cycles

Flame Auto Extinguish UL 94-VO

CONNECTOR WEIGHT (Each)

0.15 ounces (4.25 grams)

RoHS COMPLIANT

Complies to RoHS Standards

REQUIRED TOOLING (1)

Crimp Tool P/N 110288 *Compression Tool P/N 190048 Materials:

Plug Housing Polycarbonate

Contacts Phosphor Bronze, 0.012" thick

Load Bar Polycarbonate

Shielding Brass, Alloy 70/30, 1/4 HD

Strain Relief Thermoplastic Rubber - UL 94-VO

Finish:

Shield Tin Contacts Gold

Applicable Standards: ANSI/TIA-1096-A

ANSI/TIA/EIA 568-C.2

Notes:

(1) Please refer to T-110362 Termination Instruction Sheet for strip dimensions & instructions.