


A Division of the Angelus Corporation
 Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com
 W220 N1051 Springdale Road Waukesha, WI 53186

Approved : *JDA*
 Distribution : USER

Date : 07/14/21
 Rev : 0 (07/14/21)
 Uncontrolled if Printed

N Bulkhead Jack
 for S31601 Coax Cable



PERFORMANCE

Nominal Impedance	50 Ohms
Frequency Range	DC - 11 GHz
DW Voltage	2500 V (rms)
Insulation Resistance	5000 Megaohms min

CONSTRUCTION

Materials:

Body	Brass
Insulator	PTFE
Contact Pin	Brass
Lock Washer	Brass
Contact Pin	Phosphor Bronze
Barrel	Brass
Ferrule	Brass
Hex Nut	Brass
Gasket	Silicon Rubber

CONNECTOR WEIGHT (Each)

1.34 ounces (31.9 grams)

RoHS COMPLIANT

Complies to RoHS Standards

Finish :

Ferrule, Body	Nexcote
Center Contact	Gold

INSTALLATION

Center Contact

Solder

APPLICABLE STANDARDS

MIL-348

Crimp Ferrule

M22520 / 5-01 Hex Crimp Tool
 M22520 / 5-08 Hex Crimp Die Set
 Cavity A (.128" Hex)

Notes :

- 1) A 1.0" piece of Raychem ATUM heat shrink P/N ATUM- 8/2-1.0" provided with connector for purpose of strain relief & moisture protection.
- 2) Please refer to T-111071 Termination Instruction sheet for strip dimensions & instructions.