



PIC Wire & Cable <i>A Division of the Angelus Corporation</i> Ph 262-246-0500 Fax 262-246-0450 PO Box 330 Sussex, WI 53089	Connector Specification	190945
	Approved 	Date 09/08/10 Rev. 2 (05/29/13)
	Distribution : USER	Uncontrolled Document

Mini-BNC Straight Plug
for V78209



Features Not Shown: Gasket in front

PERFORMANCE

Impedance	75 Ohms
Frequency Range	0 - 3 GHz
Voltage Rating	300 VRMS
Insulation Resistance	5000 Megohms

CONNECTOR WEIGHT (Each)

.34 ounces (9.8 grams)

RoHS COMPLIANT

Complies to RoHS Standards

INSTALLATION

Crimp Tooling:

Center Contact M22520 / 1 - 01 Tool,
Selector Dial @ # 5
Recommended Positioner :
PIC # 110656 (Daniels # TH729),
Selector @ Red

Crimp Ferrule M22520 / 5 - 01 Tool,
Die Set M22520 / 5 - 59 ,
PIC P/N 110697
Cavity A (.255" hex)

CONSTRUCTION

Materials:

Body	Brass, ASTM-B16
Center Contact	Brass, ASTM-B16
Outer Contact	Beryllium Copper, ASTM-B196
Ferrule	Brass, ASTM-B16
Dielectric	TFE Fluorocarbon, ASTM-D1710

Finish :

- Body, Ferrule	Nickel
- Center Contact	Gold

Notes :

1) Please refer to T-1909XX Termination Instruction sheet for strip dimensions & instructions.